



Borehole **30-07-07**

Log Event **A**

**Borehole Information**

Farm : <u>C</u>	Tank : <u>C-107</u>	Site Number : <u>299-E27-90</u>
N-Coord : <u>42,815</u>	W-Coord : <u>48,485</u>	TOC Elevation : <u>646.00</u>
Water Level, ft :	Date Drilled : <u>10/31/1974</u>	

**Casing Record**

Type : <u>Steel-welded</u>	Thickness : <u>0.280</u>	ID, in. : <u>6</u>
Top Depth, ft. : <u>0</u>	Bottom Depth, ft. : <u>97</u>	

**Borehole Notes:**

Borehole 30-07-07 was drilled in October 1974 to a depth of 100 ft with 6-in. casing. The casing thickness is assumed to be 0.280 in., on the basis of the published thickness for schedule-40, 6-in. steel tubing. No information concerning grouting or perforations was available; therefore, it is assumed that the borehole was not grouted or perforated. The zero reference is top of the casing and is even with the ground surface.

**Equipment Information**

Logging System : <u>2</u>	Detector Type : <u>HPGe</u>	Detector Efficiency: <u>35.0 %</u>
Calibration Date : <u>10/1996</u>	Calibration Reference : <u>GJO-HAN-13</u>	Logging Procedure : <u>P-GJPO-1783</u>

**Log Run Information**

Log Run Number : <u>1</u>	Log Run Date : <u>03/17/1997</u>	Logging Engineer: <u>Bob Spatz</u>
Start Depth, ft.: <u>98.5</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>60.0</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>
Log Run Number : <u>2</u>	Log Run Date : <u>03/18/1997</u>	Logging Engineer: <u>Bob Spatz</u>
Start Depth, ft.: <u>61.0</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>39.0</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>
Log Run Number : <u>3</u>	Log Run Date : <u>03/18/1997</u>	Logging Engineer: <u>Bob Spatz</u>
Start Depth, ft.: <u>40.0</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>12.0</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>
Log Run Number : <u>4</u>	Log Run Date : <u>03/19/1997</u>	Logging Engineer: <u>Bob Spatz</u>
Start Depth, ft.: <u>13.0</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>0.0</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>



Borehole **30-07-07**

Log Event A

---

### Analysis Information

---

Analyst : D.L. Parker

Data Processing Reference : MAC-VZCP 1.7.9

Analysis Date : 08/20/1997

#### Analysis Notes :

This borehole was logged by the SGLS in four log runs. The pre- and post-survey field verification spectra met the acceptance criteria established for the peak shape and detector efficiency, confirming that the SGLS was operating within specifications. The energy calibration and peak-shape calibration from these spectra were used to establish the channel-to-energy parameters used in processing the spectra acquired during the logging operation. There was some gain drift and it was necessary to adjust the established channel-to-energy parameters during processing of log data to maintain proper peak identification.

Casing correction factors for a 0.280-in.-thick steel casing were applied during analysis.

The only man-made radionuclide detected in this borehole was Cs-137. The presence of Cs-137 was measured continuously from the ground surface to 15.5 ft, intermittently from 58.5 to 72 ft, and at the bottom of the logged interval (98.5 ft).

The U-238 and Th-232 concentration data are absent along several short intervals throughout the length of the borehole.

The K-40 concentrations are relatively elevated from 39.5 to 41 ft. K-40 and U-238 concentrations are elevated from 47.5 to about 61 ft. Th-232 concentrations are elevated from 50 to about 62 ft and are highly variable over the depth of the borehole.

Shape factor data analysis was performed using the SGLS data from this borehole.

Additional information and interpretations of log data are included in the main body of the Tank Summary Data Report for tank C-107.

#### Log Plot Notes:

Separate log plots show the man-made and the naturally occurring radionuclides. The natural radionuclides can be used for lithology interpretations. The headings of the plots identify the specific gamma rays used to calculate the concentrations.

Uncertainty bars on the plots show the statistical uncertainties for the measurements as 95-percent confidence intervals. Open circles on the plots give the MDL. The MDL of a radionuclide represents the lowest concentration at which positive identification of a gamma-ray peak is statistically defensible.

A combination plot includes the man-made and natural radionuclides, the total gamma derived from the spectral data, and the Tank Farms gross gamma log. The gross gamma plot displays the latest available digital data. No attempt has been made to adjust the depths of the gross gamma logs to coincide with the SGLS data.

A plot showing the results of the shape factor analysis is included with the set of plots for this borehole.