

Borehole

41-03-02

Log Event A

Borehole Information

Farm : <u>SX</u>	Tank : <u>SX-103</u>	Site Number : <u>299-W23-194</u>
N-Coord : <u>35,578</u>	W-Coord : <u>75,832</u>	TOC Elevation : <u>663.00</u>
Water Level, ft :	Date Drilled : <u>10/30/1974</u>	

Casing Record

Type : <u>Steel-welded</u>	Thickness : <u>0.280</u>	ID, in. : <u>6</u>
Top Depth, ft. : <u>0</u>	Bottom Depth, ft. : <u>100</u>	

Equipment Information

Logging System : <u>2</u>	Detector Type : <u>HPGe</u>	Detector Efficiency: <u>35.0 %</u>
Calibration Date : <u>03/1995</u>	Calibration Reference : <u>GJPO-HAN-1</u>	

Logging Information

Log Run Number : <u>1</u>	Log Run Date : <u>5/4/1995</u>	Logging Engineer: <u>Kim Benham</u>
Start Depth, ft.: <u>0.0</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>88.5</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>

Log Run Number : <u>2</u>	Log Run Date : <u>5/5/1995</u>	Logging Engineer: <u>Kim Benham</u>
Start Depth, ft.: <u>97.5</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>87.5</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>

Borehole **41-03-02****Log Event A**

Analysis Information

Analyst : D.C. StromswoldData Processing Reference : Data Analysis Manual Ver. 1Analysis Date : 7/19/1995**Analysis Notes :**

Borehole 41-03-02 was logged in two log runs: run 1 from 0 to 88.5 ft, and run 2 from 97.5 to 87.5 ft. The pre- and post-survey field verification spectra showed consistent peak activities for both runs, but energy calibrations differed due to gain drift in the instrumentation. Spectra were recalibrated for energy versus channel. Each run was recorded on 0.5-ft stations with a counting time of 100-s.

The total measured casing thickness is 0.344 in. The casing correction used was that for 0.375 in.

Naturally occurring K-40, U-238, and Th-232 concentrations increased at 73 ft, apparently due to lithology changes.

Cs-137 occurred mainly from the surface to about 59 ft with the highest concentration of about 400 pCi/g at 1 ft. It was also detected in low concentrations at discontinuous locations to TD. The spectrum at the 4.0-ft depth indicated possible Eu-154 at a concentration of about 2 pCi/g.

Log Plot Notes:

Three log data plots are provided. The cesium concentration is provided in a separate plot to document the concentration and indicate the shape of the cesium distribution. The error of the cesium concentration determination is shown by error bars that represent the 95 percent confidence interval. The calculated MDA is shown on this plot as open circles. If the calculated concentration is less than the MDA, it is considered a non-detect and the concentration is not reported.

A plot of naturally occurring potassium, uranium, and thorium (K-40, U-238, and Th-232) is provided to permit correlation of these data with geologic information.

The natural gamma logs are shown in a separate plot to allow correlation of these data with the lithology. These data are also plotted with the MDA values and the error bars. On the Th-232 plot, the MDA value is shown as zero at some depth locations. This zero value was a result of an anomaly in the commercial spectrum analysis software which has been corrected by the vendor. Because the MDA calculation at these few points is not significant relative to the intended use of the thorium plot, the data were not reprocessed and corrected. Therefore, these MDA data points on the plot should be ignored.

A combination plot of individual radionuclide concentrations is provided that includes the total gamma rate calculated from the spectral data and the WHC Tank Farms gross gamma ray log data obtained from gross gamma logging systems.