



Borehole **60-02-08**

Log Event A

Borehole Information

Farm : <u>U</u>	Tank : <u>U-102</u>	Site Number : <u>299-W18-140</u>
N-Coord : <u>38,186</u>	W-Coord : <u>75,778</u>	TOC Elevation : <u>665.00</u>
Water Level, ft :	Date Drilled : <u>2/28/1976</u>	

Casing Record

Type : <u>Steel-welded</u>	Thickness, in. : <u>0.280</u>	ID, in. : <u>6</u>
Top Depth, ft. : <u>0</u>	Bottom Depth, ft. : <u>99</u>	

Borehole Notes:

According to the driller's records, this borehole was not perforated or grouted.

Equipment Information

Logging System : <u>2</u>	Detector Type : <u>HPGe</u>	Detector Efficiency: <u>35.0 %</u>
Calibration Date : <u>03/1995</u>	Calibration Reference : <u>GJPO-HAN-1</u>	Logging Procedure : <u>P-GJPO-1783</u>

Log Run Information

Log Run Number : <u>1</u>	Log Run Date : <u>10/3/1995</u>	Logging Engineer: <u>Bob Spatz</u>
Start Depth, ft.: <u>0.0</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>4.0</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>
Log Run Number : <u>2</u>	Log Run Date : <u>10/4/1995</u>	Logging Engineer: <u>Bob Spatz</u>
Start Depth, ft.: <u>3.0</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>8.5</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>
Log Run Number : <u>3</u>	Log Run Date : <u>10/4/1995</u>	Logging Engineer: <u>Bob Spatz</u>
Start Depth, ft.: <u>7.5</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>70.0</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>
Log Run Number : <u>4</u>	Log Run Date : <u>10/5/1995</u>	Logging Engineer: <u>Bob Spatz</u>
Start Depth, ft.: <u>98.0</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>69.0</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>

Borehole

60-02-08

Log Event A

Log Run Number :	<u>5</u>	Log Run Date :	<u>10/5/1995</u>	Logging Engineer:	<u>Bob Spatz</u>
Start Depth, ft.:	<u>0.0</u>	Counting Time, sec.:	<u>100</u>	L/R : <u> </u>	Shield : <u>N</u>
Finish Depth, ft. :	<u>5.0</u>	MSA Interval, ft. :	<u>0.5</u>	Log Speed, ft/min.:	<u>n/a</u>

Analysis Information

Analyst : S.E. KosData Processing Reference : P-GJPO-1787Analysis Date : 4/9/1996

Analysis Notes :

This borehole was logged in five log runs. Several logging runs were necessary because of inclement weather during which the tank farm was evacuated, and because of problems with the logging equipment. The pre- and post-field verification spectra indicate that the logging system was operating properly during data collection. The energy/channel drift observed during the logging runs did not exceed the search parameters of the processing software, and multiple energy calibrations were not required to process the data. Data overlaps occurred when the same depth intervals were logged between log runs. The calculated concentrations were within the statistical uncertainty of the measurements, indicating acceptable repeatability.

The casing thickness is presumed to be 0.280 inch (in.), on the basis of published thickness for schedule-40, 6-in. steel casing. Casing-correction factors for a 0.25-in.-thick steel casing were applied during analysis.

Cs-137 was the only man-made radionuclide detected. It occurred continuously from the ground surface to a depth of 17.5 ft and intermittently from 20 to 28 ft. Concentrations in the continuous zone ranged between less than 0.2 and almost 5.5 pCi/g.

Details regarding the interpretation of the data for this borehole are presented in the Tank Summary Data Report for tank U-102.

Log Plot Notes:

Separate log plots show the man-made (e.g., Cs-137) and the naturally occurring radionuclides (K-40, U-238, and Th-232). The natural radionuclides can be used for lithology interpretations. The headings of the plots identify the specific gamma rays used to calculate the concentrations.

A combination plot includes both the man-made and natural radionuclides, in addition to the total gamma derived from the spectral data and the Westinghouse Hanford Company (WHC) Tank Farms gross gamma log. The gross gamma plot displays the latest available digital data from WHC with no attempt to adjust the depths to coincide with the SGLS data.

Uncertainty bars on the plots show the statistical uncertainties for the measurements as 95-percent confidence intervals. Open circles on the plots give the minimum detection level (MDL). The MDL of a radionuclide represents the lowest concentration at which positive identification of a gamma-ray peak is statistically defensible.